

# Technical specifications

## LUBRICANTS AND FLUIDS

Part	Variant	Specification
Engine oil	2.0L Petrol	SAE 5W-30 engine oil meeting specification WSS M2C913-B or C.
	3.0L (SC) Petrol	SAE 5W-30 engine oil meeting specification WSS M2C913-C is preferred. Oil meeting ACEA A1/B1 or ACEA A3/B3 specification may be used.
	5.0L (SC) Petrol	SAE 5W-20 engine oil meeting specification WSS M2C925-A only.
	Diesel <b>with</b> Diesel particulate filter	SAE 5W-30 engine oil meeting specification WSS M2C934-B only.
	Diesel <b>without</b> Diesel particulate filter	SAE 5W-30 engine oil meeting specification WSS M2C913-B only or WSS-M2C913-C.
Power steering fluid	All vehicles	Mobil ATF320 PAS fluid.
Brake fluid	All vehicles	Shell DOT4 ESL is preferred. If unavailable, a low viscosity, synthetic compatible DOT4 brake fluid that meets ISO 4925 class 6 specification may be used.
Washer fluid	All vehicles	Screen wash with frost protection, diluted with clean water as specified on the bottle.
Engine coolant fluid	All vehicles	50% mixture of water and antifreeze specification WSS M97B44 (coloured orange) Extended Life Coolant.
If in doubt about the required specification of a lubricant or fluid for your vehicle, seek advice from your Dealer/Authorised Repairer.		