AVOIDING FLAT SPOTS

In order to minimise flat spotting, the tyre pressures can be increased to the maximum as stated on the tyre sidewall, for the period when the vehicle is stationary. Tyres must be returned to the specified running pressures before driving.

TYRE DEGRADATION

Tyres degrade over time due to the effects of ultraviolet light, extreme temperatures, high loads, and environmental conditions. It is recommended that tyres are replaced at least every six years, but they may require replacement more frequently.

USING WINTER TYRES

In many countries legislation exists that requires the use of winter tyres during specified periods of the year.

Note: M+S (mud and snow) tyres have a recognised level of winter performance and need not be replaced.



The M+S marking on the tyre sidewall indicates an 'all season' tyre designed for use all year round, including cold temperatures, snow and ice

Note: Dedicated winter tyres often have a lower speed rating than the original equipment tyres and the vehicle must therefore be driven within the speed limitation of the winter tyre.



This symbol identifies dedicated winter tyres, which can be fitted if optimum winter traction is required, or the vehicle is to be used in more extreme winter conditions

Winter tyres must be fitted to all 4 wheels.

For optimum traction, tyres should be run in for at least 160 kilometres (100 miles) on dry roads prior to driving on snow or ice.

Use of dedicated winter tyres may require a change of wheel size, depending on original choice of wheel. All 4 wheels must be changed.

If fitted with standard rubber valves, the Tyre pressure monitoring system (TPMS) warning lamp will flash for 75 seconds and then remain illuminated. The message centre will also display TYRE PRESSURE MONITORING SYSTEM FAULT.

When the original wheels and tyres are refitted, the vehicle will need to travel a short distance to reset the TPMS and extinguish the warning lamp.

Do not exceed 240 km/h (150 mph) when using Jaguar approved winter tyres.

Approved winter tyres

Front:

245/45R19 102V Prirelli Sottozero Series II, 245/45R20 99V Prirelli Sottozero Series II.

Rear:

275/40R19 105V Prirelli Sottozero Series II, 275/35R20 102V Prirelli Sottozero Series II.