

ENGINE SPECIFICATIONS

	Number of cylinders	Displacement (cc)	Compression ratio
2.0L Petrol	4	1999	10:1
3.0L Petrol (SC)	6	2995	10.5:1
5.0L Petrol (NA)	8	5000	11.5:1
5.0L Petrol (SC)	8	5000	9.5:1
3.0L Diesel	6	2993	16.1:1

NA - Normally Aspirated, **SC** - Supercharged.

LUBRICANTS AND FLUIDS

Part	Engine variant	Specification
Engine oil	2.0L Petrol	SAE 5W-30 engine oil meeting specification WSS M2C913-C is preferred.
	3.0L Petrol	SAE 5W-30 engine oil meeting specification WSS M2C913-C is preferred. Oil meeting ACEA A1/B1 or ACEA A3/B3 specification may be used.
	5.0L Petrol	SAE 5W-20 engine oil meeting specification WSS M2C925-A only.
	3.0L Diesel with Diesel particulate filter	SAE 5W-30 engine oil meeting specification WSS M2C934-B only.
	3.0L Diesel without Diesel particulate filter	SAE 5W-30 engine oil meeting specification WSS-M2C913-B or WSS-M2C913-C.
Power steering fluid	All vehicles	Mobil ATF320 PAS fluid.
Brake fluid	All vehicles	Shell DOT4 ESL is preferred. If unavailable, a low viscosity, synthetic compatible DOT4 brake fluid that meets ISO 4925 specification may be used.
Washer fluid	All vehicles	Screen wash with frost protection, diluted with clean water as specified on the bottle.
Engine coolant fluid	All vehicles	50% mixture of water and antifreeze, specification WSS M97B44 (coloured orange) Extended Life Coolant.

If in doubt about the required specification of a lubricant or fluid for your vehicle, seek advice

from your Dealer/Authorised Repairer.