

## GLOBAL OPENING

Press and hold the unlock button on the Jaguar Smart Key for 3 seconds. The vehicle will unlock and the alarm will be disarmed immediately. After the 3 seconds all of the windows will open.

To stop window movement during global opening when using the Smart Key, press any of the buttons on the Smart Key.

**Note:** *Global opening can be enabled/disabled via the Security/ vehicle settings menu on the touch screen. See 52, VEHICLE SETTINGS.*

## DRIVE-AWAY LOCKING

Locks all the doors when the vehicle exceeds a set speed. One of three set speeds can be selected via the Security/ vehicle settings menu on the touch screen. See 52, VEHICLE SETTINGS. Use of the central locking/ unlocking buttons (see 202, DRIVER CONTROLS), will override the drive-away locking feature for the rest of a journey.

If a door is individually unlocked and opened, all doors will relock when the open door is subsequently closed.

**Note:** *Drive-away locking can be enabled/ disabled via the Security/ vehicle settings menu on the touch screen. See 52, VEHICLE SETTINGS.*

## STEERING COLUMN LOCK

The steering column has an electronic lock, which locks and unlocks in conjunction with the vehicle Locking/Alarm system. The steering column lock also locks when the ignition is switched off, after a time delay. If the steering column lock malfunctions, **Steering Column Locked** is displayed in the message centre. If this occurs:

1. Lock and then unlock the vehicle using the Smart Key.

2. Try again to unlock the steering column lock, by turning the steering wheel gently to the left and right.
3. If the malfunction persists, seek qualified assistance immediately.

## REMOTE KEY FOB CARE

 **To prevent accidental operation, which may result in an injury, never leave the Jaguar Smart Key in the vehicle if children or animals are also left in the vehicle.**

 Do not expose to extremes of heat, dust, humidity or fluids. Do not leave the transmitter exposed to direct sunlight.

The emergency key blade number is recorded on an attached label, which should be peeled off and affixed to the correct area on the Security Card, supplied in the literature pack. Keep the Security Card safe, but not in the vehicle.

The operational range of the Smart Key varies considerably, depending on atmospheric conditions and interference from other devices.

**Note:** *The radio frequency used by the Smart Key may be used by other devices (e.g. medical equipment). This may prevent the Smart Key from operating correctly.*