

Technical specifications

WHEEL ALIGNMENT DATA (CHINA)

Front	Left-hand side		Right-hand side	
	Min	Max	Min	Max
Camber	-1° 09'	+0° 21'	-1° 21'	+0° 09'
Castor	+6° 02'	+7° 32'	+6° 02'	+7° 32'
Min		Max		
Toe (total)	-0° 02'		+0° 22'	

Rear	Left-hand side		Right-hand side	
	Min	Max	Min	Max
Camber	-1° 20'	+0° 10'	-1° 20'	+0° 10'
Castor	Non-adjustable		Non-adjustable	
Min		Max		
Toe (total)	+0° 03'		+0° 27'	

Note: All above figures are with the vehicle at kerb weight (full fuel, full fluids, no occupants or luggage).

Note: Tyre pressures must be inflated to normal pressure settings.

BRAKE PEDAL TRAVEL (CHINA)

The brake pedal travel is set at the factory and is non-adjustable.

ACCESSORY WHEELS AND TYRES



Contact your Dealer/Authorised Repairer before fitting any accessory wheels and tyres.

Note: Use this table to record accessory wheel and tyre information.

A _____ B _____

C _____

SJ1719

- A. Front tyre pressure.
- B. Rear tyre pressure.
- C. Wheel and tyre information (size, speed rating, etc.).