Navigation system

Note: As you approach a junction, in addition to the voice guidance, an inset on the map will display an enlarged view of the junction.

CANCEL GUIDANCE

To cancel guidance, select Menu.

On the Menu screen select **Cancel Guidance** and **Yes** to confirm

OHICK POLSELECTION

Touch the Map screen to display the POI button

Touch the **POI** (Point of interest) button. The screen shows six suggested categories, five of which can be selected as quick points of interest

Note: The POI icons will not be shown if the map zoom level is greater than 1 km (½ mile). Select a Quick POI category, or select **More** to see further POIs.

Select the five POIs you wish to see when the Quick POIs are displayed.

Select **OK**. The map screen with the POI icon(s) is displayed.

CALIBRATION

If the vehicle has been moved without being driven (e.g. by rail or trailer), the vehicle position/direction may need to be recalibrated, see 118, POSITION/DIRECTION.

If the tyres have been changed, the distance measuring system used by the navigation system will need to be recalibrated.

Select **Calibration** from the **Navigation Setup** menu.

Select the **Distance** button if the tyres have been changed. The system automatically recalibrates its distance measurements accordingly.

POSITION/DIRECTION

If the vehicle has been moved without being driven (e.g. by rail or trailer), the vehicle position/direction may need to be recalibrated.

Select **Calibration** from the **Navigation Setup** menu.

Select the Position/Direction button.

Touch the appropriate arrow icons to scroll the map until the vehicle position is in the correct location, then select **OK** to confirm.

The map showing the heading adjustment arrows is displayed. Adjust the heading by touching the arrows until the navigation symbol shows the correct alignment. Select **OK** to confirm the new heading.

RESTORE SYSTEM DEFAULTS

If you have made any changes to the system's default settings, speed settings etc.

Select Navigation Setup from the Main menu.

Select Restore Default.

Select **Default** and **Yes** to confirm