Note: *As you approach a junction, in addition to the voice guidance, an inset on the map will display an enlarged view of the junction.*

CANCEL GUIDANCE

To cancel guidance, select **Menu**.

On the Menu screen select **Cancel Guidance** and **Yes** to confirm.

QUICK POI SELECTION

Touch the Map screen to display the POI button.

Touch the **POI** (Point of interest) button. The screen shows six suggested categories, five of which can be selected as quick points of interest.

Note: *The POI icons will not be shown if the map zoom level is greater than 1 km (½ mile).*

Select a Quick POI category, or select **More** to see further POIs.

Select the five POIs you wish to see when the Quick POIs are displayed.

Select **OK**. The map screen with the POI icon(s) is displayed.

CALIBRATION

If the vehicle has been moved without being driven (e.g. by rail or trailer), the vehicle position/direction may need to be recalibrated, see **118, POSITION/DIRECTION**.

If the tyres have been changed, the distance measuring system used by the navigation system will need to be recalibrated.

Select **Calibration** from the **Navigation Setup** menu.

Select the **Distance** button if the tyres have been changed. The system automatically recalibrates its distance measurements accordingly.

POSITION/DIRECTION

If the vehicle has been moved without being driven (e.g. by rail or trailer), the vehicle position/direction may need to be recalibrated.

Select **Calibration** from the **Navigation Setup** menu.

Select the **Position/Direction** button.

Touch the appropriate arrow icons to scroll the map until the vehicle position is in the correct location, then select **OK** to confirm.

The map showing the heading adjustment arrows is displayed. Adjust the heading by touching the arrows until the navigation symbol shows the correct alignment. Select **OK** to confirm the new heading.

RESTORE SYSTEM DEFAULTS

If you have made any changes to the system's default settings, speed settings etc.

Select **Navigation Setup** from the **Main** menu.

Select **Restore Default**.

Select **Default** and **Yes** to confirm.