

DISABILITY MODIFICATIONS

⚠ WARNING

Occupants with disabilities that may require the vehicle to be modified must contact a Jaguar Dealer/Authorized Repairer before any modifications are made. Failure to do so can result in the vehicle being rendered unsafe, potentially leading to personal injury.

Modifications may adversely affect the vehicle which can lead to loss of control, resulting in a crash.

(USA only) If you are considering modifying your vehicle in any way to accommodate a disability, for example by altering or adapting the driver's or passenger's seat(s) or air bag system, please contact Jaguar Cars at:

Jaguar Cars Customer Relations Center
555 MacArthur Blvd
Mahwah
New Jersey 07430-2327
1-800-4JAGUAR OPTIONS 9.

PARTS AND ACCESSORIES

⚠ WARNING

The use of non-approved parts and accessories, or the carrying out of non-approved alterations or conversions, may be dangerous and could affect the safety of the vehicle and occupants and also invalidate the terms and conditions of the vehicle warranty.

⚠ WARNING

Jaguar will not accept any liability for death, personal injury or damage to property which may occur as a result of the use of non-approved accessories or the carrying out of non-approved conversions to Jaguar vehicles.

NOTICE

Your vehicle is not designed for use with a roof rack. Do not fit a roof rack to the vehicle, as damage may result.

AIR BAG SYSTEM

⚠ WARNING

The components that make up the air bag system are sensitive to electrical or physical interference, either of which could easily damage the system and cause inadvertent operation or a malfunction of the air bag module.

⚠ WARNING

Certain components of this vehicle such as air bag modules and seat belt pretensioners may contain Perchlorate Material - Special handling may apply for service or vehicle end of life disposal. See: www.dtsc.ca.gov/hazardouswaste/perchlorate.

To prevent malfunction of the air bag system always consult your Dealer/Authorized Repairer before fitting any of the following:

- Electronic equipment such as a cell phone, two-way radio or in-car entertainment system.
- Accessories attached to the front of the vehicle.
- Any modification to the front of the vehicle.
- Any modification involving the removal or repair of any wiring or component in the vicinity of any of the air bag system components, including the steering wheel, steering column, instrument or facia panels.
- Any modification to the facia panels or steering wheel.

OWNER MAINTENANCE

NOTICE

Any significant or sudden drop in fluid levels, or uneven tire wear, should be reported to a qualified technician without delay.

In addition to the routine services and inspections, a number of simple checks must be carried out more frequently. These checks can be carried out by the owner and advice is given on the pages that follow.

DAILY CHECKS

- Operation of lamps, horn, direction indicators, wipers, washers and warning indicators.
- Operation of seat belts and brakes.
- Look for fluid deposits underneath the vehicle that might indicate a leak. Condensation drips from the air conditioning are normal.

WEEKLY CHECKS

- Engine oil level.
- Engine coolant level.
- Brake fluid level.
- Power steering fluid level.
- Screen washer fluid level.
- Tire pressures and condition.
- Operate air conditioning.

Note: *The engine oil level should be checked more frequently if the vehicle is driven for prolonged periods at high speeds.*

ARDUOUS DRIVING CONDITIONS

When a vehicle is operated in severe or arduous conditions, more frequent attention must be paid to servicing requirements. Refer to your Passport to Service for details or contact your Dealer/Authorized Repairer for advice.

SAFETY IN THE GARAGE

⚠ WARNING

If the vehicle has been driven recently, do not touch exhaust and cooling system components until the engine has cooled.

⚠ WARNING

Never leave the engine running when the vehicle is in a garage. Exhaust gases are poisonous and can cause unconsciousness and death if inhaled.

⚠ WARNING

Do not work beneath the vehicle with a jack as the only means of support.

⚠ WARNING

Keep your hands and clothing away from drive belts, pulleys and fans. Some fans may continue to operate after the engine has stopped.

⚠ WARNING

Remove metal wrist bands and jewelry, before working in the engine compartment.

⚠ WARNING

Do not touch electrical leads or components while the engine is running, or with the starter switch turned on.

⚠ WARNING

Do not allow tools or metal parts of the vehicle to make contact with the battery leads or terminals.

FUEL SYSTEM

⚠ WARNING

Under no circumstances should any part of the fuel system be dismantled or replaced by anyone other than a suitably qualified vehicle technician.

⚠ WARNING

Ensure sparks and naked lights are kept away from the engine compartment.

⚠ WARNING

Wear protective clothing, including, where practicable, gloves made from an impervious material.

USED ENGINE OIL

⚠ WARNING

Prolonged contact with engine oil may cause serious skin disorders, including dermatitis and cancer of the skin. Always wash thoroughly after contact.

UNBLOCKING WASHER JETS

⚠ WARNING

Do not operate the washer jets during adjustment. Windshield washer fluid may cause irritation to the eyes and skin. Always read and observe the washer fluid manufacturers instructions.

If a washer jet becomes blocked, use a thin strand of wire to unblock the jet by inserting the wire into the jet. Ensure that the wire is completely removed after unblocking.

LAMP FAILURE

Headlamp unit:

⚠ WARNING

High voltage is required to ignite the gas and metal vapor which are used to power Xenon lamps. Contact with this voltage can cause serious injury. Replacement or maintenance of Xenon lamps should only be carried out by suitably qualified personnel.

⚠ WARNING

Xenon lamp units operate at a very high temperature. Ensure that the lamp units have cooled before attempting to touch them.

NOTICE

All other lamps within the headlamp unit are LEDs and should only be replaced by a Dealer/Authorized Repairer.



Correct disposal of the Xenon lamp unit should be referred to your Dealer/Authorized Repairer or your local authority.

Side, repeater and rear lamps:

NOTICE

These lamps are LED units and should only be replaced by a Dealer/Authorized Repairer.

WINDOW RESET

The windows will need to be reset if the battery is disconnected, becomes discharged or power supply is interrupted.

Once the power supply is restored, reset the windows as follows, making sure the doors and (if fitted), the convertible roof is closed:

1. Close the window fully.
2. Release the switch, then lift it to the close position and hold for 2 seconds.
3. Open the window fully.

4. Release the switch, then push it to the open position and hold for 2 seconds.
5. Lift and release the switch to operate the one-touch function.
6. Repeat the procedure on each window.

WARNING TRIANGLE

Coupe: The warning triangle is located under the luggage compartment floor.

Convertible: The warning triangle is stowed in the luggage compartment lid.

FIRST AID KIT

Your Dealer/Authorized Repairer can supply a first aid kit.

FIRE EXTINGUISHER

If supplied, the fire extinguisher will be located either in the luggage compartment, or mounted to the front passenger seat. For instructions on how to use the extinguisher and it's maintenance, see the label on the extinguisher.

REPAIRING MINOR PAINT DAMAGE

Regularly inspect the paintwork for damage. Any stone chips, fractures, or deep scratches, in the paint/bodywork should be repaired promptly. Bare metal will corrode quickly, and if left untreated can result in expensive repairs.

CLEANING THE ALLOY WHEELS

NOTICE

Only use approved wheel cleaning products.

CLEANING THE EXTERIOR

NOTICE

Some high pressure cleaning systems are sufficiently powerful to penetrate door and window seals, and damage trim and door locks. Never aim the water jet directly at the engine air intake, heater air intakes, body seals or at any components which may be damaged.

NOTICE

Do not use a power wash system in the engine bay area as it may cause damage.

NOTICE

Ensure that you read and comply with all warnings and product instructions supplied with any cleaning products.

NOTICE

Never use cleaning products which are not approved for use on vehicles.

Convertible roof:

Do not leave the convertible roof in the open (folded) position for longer than is necessary, as in certain circumstances permanent soiling along the folds may occur.

Cleaning: Every 1,000 miles (1,600 km) vacuum clean and wash the convertible roof. Your Dealer/Authorized Repairer will be able to recommend suitable products.

Reproofing: Every 5,000 miles (8,000 km) reproof the convertible roof material. Your Dealer/Authorized Repairer will be able to recommend suitable products.

WASHING THE VEHICLE PAINTWORK

NOTICE

Substances which are corrosive can damage the vehicle's paintwork. Any such deposits should be removed as soon as possible to prevent damage.

USING AN AUTOMATIC WASH

NOTICE

Commercially operated automatic car washes, jet washes and power-operated mops, are not recommended.

UNDER HOOD CLEANING

NOTICE

Do not use a high pressure washer or steam cleaner in the engine compartment.

NOTICE

Ensure that the brake fluid reservoir is kept dry at all times. Only use a clean, dry cloth to clean the brake fluid cap and reservoir.

CLEANING GLASS SURFACES

Clean the rear window with a soft cloth to avoid damaging the heating element. Do not scrape the glass or use any abrasive cleaning fluid.

Mirror glass is particularly susceptible to damage. Wash with soapy water. Do not use abrasive cleaning compounds or metal scrapers to remove ice.

CLEANING THE REAR GLASS

To avoid damaging the heating and radio elements (coupe only), when cleaning the inside of the rear screen use only a damp cloth or chamois leather. Do not use solvents or sharp objects to clean the glass.

REMOVING GREASE AND TAR

Remove grease or tar with Jaguar Tar Remover or methylated spirit (alcohol). White spirit is also effective, but must not be applied to rubber, particularly the windshield wiper blades.

NOTICE

Ensure that after using methylated or white spirit, the area is washed immediately with soapy water, to remove all traces of spirit.

POLISHING

NOTICE

Chrome polish, or other abrasive cleaners, must not be used on the vehicle's brightwork.

It is recommended that the vehicle is polished regularly using Jaguar polish and a polishing cloth.

CLEANING THE INTERIOR

CAUTION

Some cleaning products contain substances that are harmful and can cause health problems if used incorrectly. They may also cause damage to the interior of the vehicle.

NOTICE

The steering wheel center pad and other areas containing air bags should only be cleaned sparingly with a damp cloth, warm water and a non-detergent soap.

LEATHER

NOTICE

Some materials are prone to dye transfer, which can cause unsightly discoloration of lighter colored leathers. Affected areas should be cleaned and re-protected as soon as possible.

To prevent ingrained dirt and staining, inspect the seat upholstery regularly and clean every one to two months, as follows:

- Wipe off fine dust from the seat surfaces using a clean, damp, non-colored cloth. Change frequently to a clean area of cloth, to avoid abrasive action on the leather surface. Avoid over-wetting.

- If this is not sufficient, use a cloth which has been dampened with warm soapy water and then wrung out. Use only mild non-caustic soap.
- Use Jaguar Leather Cleaner for heavily soiled areas. Dry off and rub with a clean soft cloth, changing surfaces regularly.

Use Jaguar Leather Cleaner several times a year to maintain its appearance and suppleness. The cleaner will nourish and moisturize and help to improve the surface protective film against dust and substances.

- Do not use solvents. Do not use detergents, furniture polish or household cleaners. While these products may initially give impressive results, their use will lead to rapid deterioration of the leather and will invalidate the warranty. Jaguar recommend a basic set of products that have been specially selected for the type of leather in your vehicle.
- Dark clothing may stain leather seats just like other upholstery products.
- Sharp objects such as belts, zip fasteners, rivets, etc., can leave permanent scratches and scratch marks on the leather surface.
- Unless spillages such as tea, coffee or ink are washed away immediately, permanent staining may have to be accepted.

If a valet service is used, ensure that the specialist concerned is aware of, and follows, these instructions precisely.

CLEANING FABRIC UPHOLSTERY

NOTICE

Never use soap, ammonia, bleach or other cleaners intended for use on hard surfaces.

NOTICE

Do not use upholstery cleaner on electrical equipment such as facia switches.

NOTICE

When cleaning around electrical equipment such as switches, ensure that fluids do not leak into any gaps around the components or between panels or trim.

Use Jaguar Upholstery Cleaner, following the instructions. Avoid over-wetting.

REMOVING STAINS

Most stains on woollen fabric can be removed if treatment is carried out immediately, before the stain has a chance to dry-in.

Most stains can be treated with one of three cleaning fluids: Jaguar Upholstery Cleaner, dry cleaning fluid or clean water. Follow the instructions on the package.

INSTRUMENT PANEL, CLOCK AND AUDIO EQUIPMENT

Only use a soft dry cloth to clean the instrument panel, clock and audio equipment. Do not use cleaning fluids or sprays.

TOUCH SCREEN

NOTICE

Do not use abrasive cleaners on the touch screen. For approved cleaning products, contact your Dealer/ Authorized Repairer.

CARPETS AND MATS

Marks or stains can be removed by gentle scrubbing with a weak solution of soap and warm water.

For more stubborn stains a commercially available carpet cleaner should be used.

SEAT BELTS

WARNING

Do not allow any water, cleaning products, or fabric from cloths to enter the seat belt mechanism. Any substance which enters the mechanism may affect the performance of the seat belt in an impact.

Extend the seat belts fully, then use warm water and a non-detergent soap to clean. Allow the seat belts to dry naturally while fully extended and do not allow the belts to retract until fully dry.

***Note:** While cleaning the seat belt, take the opportunity to examine the webbing for damage and wear. Any wear or damage should be reported to, and rectified by, a Dealer/Authorized Repairer.*

AIR BAG MODULE COVERS

WARNING

Air bag covers should only be cleaned using a slightly dampened cloth, and a small amount of upholstery cleaner.

WARNING

Any substance which enters the mechanism, can prevent correct deployment of an air bag during an impact.

PREPARATION FOR WINTER

Before the onset of winter, it is advisable to coat the convertible roof seals and respective body seals with a compound, such as Carbaflo KSP 105, to aid operation in freezing conditions. This action will need to be repeated at the start of each winter to maintain protection.

Care must be taken so that the compound does not come into contact with the convertible roof material. For further advise you should contact your Dealer/Authorized Repairer.