

Approved winter tyre sizes and pressures				
Wheel size (inch)	Tyre size and make	Load index	Front pressures bar (psi, kPa)	Rear pressures bar (psi, kPa)
17	Dunlop Wintersport M3 235/55 R17 H	99	2.3 (34, 230)	2.3 (34, 230)
18	Dunlop Wintersport M3 W240 Pirelli Sotto Zero 245/45 R18 V	96 100	2.4 (35, 240)	2.4 (35, 240)
19	Dunlop Wintersport M3 W240 Pirelli Sotto Zero 245/40 R19 V	98	2.6 (38, 260)	2.6 (38, 260)
20	W240 Pirelli Sotto Zero Front - 255/35R20 V Rear - 285/30 R20 V	97	2.7 (40, 270)	2.7 (40, 270)

USING SNOW CHAINS



Only use traction devices in heavy snow conditions, on hard road surfaces.



Dynamic Stability Control (DSC) must be switched off when using traction devices.



Never exceed 50 km/h (30 mph) when traction devices are fitted.



Never fit traction devices to a temporary use spare wheel.

Jaguar approved traction devices may be used to improve traction on a hard road surface in heavy snow conditions.

If it becomes necessary to fit traction devices, the following points must be observed:

- Only Jaguar approved traction devices should be used on the vehicle. Only Jaguar approved traction devices have been tested to ensure that they do not cause damage to the vehicle. Contact your Dealer/Authorised Repairer for information.
- The wheels and tyres fitted must conform to the specifications of the original equipment.
- Full chain traction devices can be fitted to only the rear wheels.
- Do not fit a traction device to a temporary use spare wheel.
- Fit traction devices in pairs on the same axle.