

# Technical specifications

## LUBRICANTS AND FLUIDS

Part	Variant	Specification
Engine oil	2.0L petrol	SAE 5W-30 engine oil meeting specification WSS M2C913-B or C.
	3.0L petrol SC	SAE 0W-20 engine oil meeting Jaguar Land Rover specification STJLR.51.5122.  If unavailable SAE 5W-20 engine oil, meeting specification WSS-M2C925-A may be used, but not where ambient temperatures fall to lower than -20 deg C
	5.0L petrol SC	SAE 0W-20 engine oil meeting Jaguar Land Rover specification STJLR.51.5122.  If unavailable SAE 5W-20 engine oil, meeting specification WSS-M2C925-A may be used.
	Diesel <b>with</b> Diesel particulate filter	SAE 5W-30 engine oil meeting specification WSS M2C934-B.  If unavailable 5W-30 engine oil, meeting specification ACEA C2 may be used.
	Diesel <b>without</b> Diesel particulate filter	SAE 5W-30 engine oil meeting specification WSS M2C913-B or C.  If unavailable 5W-30 engine oil, meeting specification ACEA A5/B5 may be used.
Power steering fluid	All vehicles	Mobil ATF320 PAS fluid.
Brake fluid	All vehicles	Shell DOT4 ESL is preferred. If unavailable, a low viscosity, synthetic compatible DOT4 brake fluid that meets ISO 4925 class 6 specification may be used.
Washer fluid	All vehicles	Screen wash with frost protection, diluted with clean water as specified on the bottle.
Engine coolant fluid	All vehicles	50% mixture of water and antifreeze specification WSS M97B44 (coloured orange) Extended Life Coolant.
If in doubt about the required specification of a lubricant or fluid for your vehicle, seek advice from a Dealer/Authorised Repairer.		