LUBRICANTS AND FLUIDS

Part	Variant	Specification
Engine oil	2.0L petrol	SAE 5W-30 engine oil meeting specification WSS M2C913-C.
	3.0L petrol SC	SAE 5W-20 engine oil meeting specification WSS-M2C925-A. Where ambient temperatures fall to lower than -20 deg C, SAE 0W-20 engine oil meeting Jaguar Land Rover specification STJLR.51.5122 should be used.
	5.0L petrol SC	SAE 5W-20 engine oil meeting specification WSS-M2C925-A.
	Diesel with Diesel particulate filter	SAE 5W-30 engine oil meeting specification WSS M2C934-B. If unavailable 5W-30 engine oil, meeting specification ACEA C2 may be used.
	Diesel without Diesel particulate filter	SAE 5W-30 engine oil meeting specification WSS M2C913-C. If unavailable 5W-30 engine oil, meeting specification ACEA A5/B5 may be used.
Power steering fluid	All vehicles	Mobil ATF320 PAS fluid.
Brake fluid	All vehicles	Use Jaguar brake fluid. If unavailable for topping up, a Low Viscosity, DOT4 brake fluid that meets the requirements of ISO 4925 class 6 may be used.
Washer fluid	All vehicles	Screen wash with frost protection, diluted with clean water, as specified on the bottle.
Engine coolant fluid	All vehicles	50% mixture of water and antifreeze specification WSS M97B44 (coloured orange) Extended Life Coolant.
Air conditioning refrigerant	All vehicles	R-134a
If in doubt about the required specification of a lubricant or fluid for your vehicle, seek advice from a Dealer/Authorised Repairer.		