

Use of dedicated winter tyres may require a change of wheel size, depending on the original choice of wheel. All 4 wheels must be changed.


If fitted with standard rubber valves, the Tyre pressure monitoring system (TPMS) warning lamp will flash for 75 seconds and then remain illuminated. The Message centre will also display **TYRE PRESSURE MONITORING SYSTEM FAULT**.

When the original wheels and tyres are refitted, the vehicle will need to travel a short distance to reset the TPMS and extinguish the warning lamp.

Approved winter tyre sizes and pressures				
Tyre make	Tyre size	Load index	Speed rating	Tyre pressures - bar (psi, kPa)
Dunlop Winter Sport M3	235/55 R17	99	H	2.5 (36, 250)
Pirelli Sotto Zero	245/45 R18	100	V	2.5 (36, 250)
Dunlop Winter Sport M3	245/45 R18	96/100	V	2.5 (36, 250)
Pirelli Sotto Zero	245/40 R19	98	V	2.5 (36, 250)
Dunlop Winter Sport M3	245/40 R19	98	V	2.5 (36, 250)
Pirelli Sotto Zero	255/35 R20	97	V	2.5 (36, 250)
Pirelli Sotto Zero	285/30 R20	99	V	2.5 (36, 250)
Nokian Hakkapeliitta 7 (studded tyre)	245/40 R19	98	T	2.5 (36, 250)
Nokian Hakkapeliitta 7 (studded tyre)	255/35 R20	97	T	2.5 (36, 250)

If in doubt, or for further information, contact a Dealer/Authorised Repairer.

USING SNOW CHAINS

 **Only use traction devices in heavy snow conditions, on compacted snow.**

 **Dynamic Stability Control (DSC) must be switched off when using traction devices.**

 **Never exceed 50 km/h (30 mph) when traction devices are fitted.**



Never fit traction devices to a temporary-use spare wheel.

Jaguar approved traction devices may be used to improve traction in heavy snow conditions, on compacted snow.

If it becomes necessary to fit traction devices, the following points must be observed:

- Only Jaguar approved traction devices should be used on the vehicle. Only Jaguar approved traction devices have been tested to make sure that they do not cause damage to the vehicle. Contact your Dealer/Authorised Repairer for information.