

## LUBRICANTS AND FLUIDS

Part	Variant	Specification
Engine oil	All vehicles	SAE 0W-20 engine oil meeting Jaguar Land Rover specification STJLR.51.5122.
Brake fluid <sup>1</sup>	Vehicles without carbon ceramic brake rotors	Use Jaguar brake fluid. If unavailable for topping up, a Low Viscosity, DOT4 brake fluid that meets the requirements of ISO 4925 class 6 may be used.
	Vehicles with carbon ceramic brake rotors	Castrol React SRF Racing <sup>2</sup>
Washer fluid	All vehicles	Screen wash with frost protection, diluted with clean water to the ratio specified on the screen wash bottle.
Engine coolant fluid	All vehicles	50% mixture of water and antifreeze, specification WSS M97B44 (colored orange) Extended Life Coolant.
Air conditioning refrigerant	All vehicles	R1234yf
Air conditioning compressor oil	All vehicles	SP-A2

<sup>1</sup> On vehicles with carbon ceramic brake rotors, it is recommended that the brake fluid is replaced prior to using the vehicle on closed roads. It is also recommended that the brake fluid is replaced after driving the vehicle on closed roads.

<sup>2</sup>If not available, use an equivalent high performance brake fluid.

If in doubt about the required specification of a lubricant or fluid for your vehicle, seek advice from a Dealer/Authorized Repairer.