

USING WINTER TIRES

Approved winter tire sizes and pressures				
Tire make	Tire size	Load index	Speed index	Tire pressures
Pirelli Sotto Zero	245/45 R18	100	V	36 psi (2.5 bar, 250 kPa)
Pirelli Sotto Zero	275/45 R18	103	V	36 psi (2.5 bar, 250 kPa)
Dunlop Winter M3	245/40 R19	98	V	36 psi (2.5 bar, 250 kPa)
Dunlop Winter M3	275/35 R19	97	V	36 psi (2.5 bar, 250 kPa)
Pirelli Sotto Zero	255/35 R20	97	V	36 psi (2.5 bar, 250 kPa)
Pirelli Sotto Zero	285/30 R20	99	V	36 psi (2.5 bar, 250 kPa)

Note: **M+S** (mud and snow) tires have a recognized level of winter performance and need not be replaced.

The **M+S** marking on the tire sidewall indicates an 'all season' tire designed for use all year round, including cold temperatures, snow, and ice.

Note: A dedicated winter tire often has a lower speed rating than the Original Equipment (OE) tire, and the vehicle must, therefore, be driven within the speed limitation of the tire. Consult your Dealer/Authorized Repairer for further information.



This symbol identifies dedicated winter tires, which can be fitted if optimum winter traction is required, or the vehicle is to be used in more extreme winter conditions.

Winter tires must be fitted to all 4 wheels.

For optimum traction, tires should be run in for at least 100 miles (160 kilometers) on dry roads, prior to driving on snow or ice.

Use of dedicated winter tires may require a change of wheel size, depending on the original choice of wheel. All 4 wheels must be changed.

If fitted with standard rubber valves, the Tire Pressure Monitoring System (TPMS) warning lamp will flash for 75 seconds and then remain illuminated. The Message center will also display **TIRE PRESSURE MONITORING SYSTEM FAULT**.

When the original wheels and tires are refitted, the vehicle will need to travel a short distance to reset the TPMS and extinguish the warning lamp.

USING SNOW CHAINS

NOTICE

It is essential that only snow chains of the recommended type are fitted.