

RADIO FREQUENCY SPECTRUM REGULATION STATEMENTS

Service	Frequency Band	Max. Output	Antenna Position	Specific Conditions
4m VHF	70 - 85 MHz	30 W/CW 40 W/AM	Anywhere on the metallic part of the roof.	Transmitter, harness, and antenna installation to the requirements of ISO/TS 21609.
2m VHF	142 - 175 MHz	30 W/CW 40 W/AM	Anywhere on the metallic part of the roof.	Transmitter, harness, and antenna installation to the requirements of ISO/TS 21609.
TETRA	380 - 422 MHz	10 W/CW 10 W/PM	Anywhere on the metallic part of the roof.	Transmitter, harness, and antenna installation to the requirements of ISO/TS 21609.
UHF	450 - 470 MHz	10 W/CW	Anywhere on the metallic part of the roof.	Transmitter, harness, and antenna installation to the requirements of ISO/TS 21609.
Bluetooth	2400 - 2483.5 MHz	10 mW	Anywhere on the vehicle.	Transmitter, harness, and antenna installation to the requirements of ISO/TS 21609.
Road Telematics	5795 - 5815 MHz	2 W eirp	Anywhere close to a glazed area that does not contain antennas or conductive glass.	Transmitter, harness, and antenna installation to the requirements of ISO/TS 21609.
Road Telematics	63 - 64 GHz	2 W eirp	Anywhere close to a glazed area that does not contain antennas or conductive glass.	Transmitter, harness, and antenna installation to the requirements of ISO/TS 21609.

South Korea only

Omnidirectional transmission or point-to-multipoint transmission is prohibited according to the law.